

**Series III High Performance
Dual 10" Bandpass Subwoofer**

- **Extended Low Frequency Response**
- **High Output for Superb Special Effects**
- **Ideal for Audio Visual Systems**

The **KSI 210-BP** is a dual 10" bandpass subwoofer system. It has been designed for efficient high impact bass response within a limited frequency range. **KSI's** three chamber bandpass design allows maximum output in a modest sized enclosure. Applications include AV systems, special effects and high end home theater.

The **KSI 210-BP** features two of our high power 1058-8 10" cast frame transducers. We designed these drivers to produce very smooth extended low frequency reproduction in a compact enclosure. A heavy magnet structure and 4 layer vented voice coil assures ample heat dissipation when high electrical inputs are applied. Achieving high output bass reproduction is routine when combined with our optimally vented bandpass enclosure. All **KSI** enclosures utilize our state of the art CNC machining techniques. Our enclosures are manufactured to the tightest tolerances and are flooded with glue at all joints to assure an air tight and vibration free cabinet. Since an air tight enclosure is so important to quality bass reproduction, all **KSI** transducers are sealed to the baffle with silicone sealant.

As always, all **KSI loudspeakers** may be used in combination with the **210-BP**, providing unlimited solutions for your audio environment. Finally, all **KSI** loudspeakers are completely assembled, saving you precious time and money for fast and easy installation.

**Specifications**

Frequency Response	41-290 HZ +/- 4 db
Sensitivity	94 db (1w/1m)
Power Capacity, watts	200 RMS; 300 Program
Crossover Frequency	Up to 250 HZ active
Nominal Impedance	8 ohms
Nominal Dispersion	At least 130 degrees conical
Low Frequency Transducer	2-10" w/ 2" voice coil
Tuning	Optimally vented bandpass
Enclosure Dimensions	28" h x 13.5" w x 12" d
Enclosure Construction	3/4" MDF w/internal stiffeners
Finish	Black lacquer w/black grille
Electrical Input	Dual gold plated binding post
Weight	58 lbs.