


501-WM

Series III Wall Mount Loudspeaker

- **Very Smooth Frequency Response**
- **Fast & Easy to Install**
- **Fully Assembled**
- **Cost Effective**



The grille on the 501-WM is acoustically transparent and will blend with any decor.



Specifications

Frequency Response	60-20,000 HZ +/- 4 db
Sensitivity	90 db (1w/1m)
Power Capacity, watts	50 RMS; 90 Program
Crossover Frequency	3500 HZ @ 6db/octave
Nominal Impedance	8 ohms
Nominal Dispersion	At least 110 degrees up to 6000 HZ
Low Frequency Transducer	5.25" - 1.25" voice coil
High Frequency Transducer	1" titanium dome
Enclosure Type	No backbox
Cutout Mounting Dimensions	10" h x 6" w
Enclosure Dimensions	11.5" h x 7.5" w x 2.5" d
Exposed Grill Dimensions	11.5" h x 7.5" w x .5" d
Baffle Construction	1/2" 9 ply Baltic birch
Mounting System	KSI continuous compression clamps
Finish	White grille & baffle
Electrical Input	Hardwire input
Weight	4 lbs.
Options	25 & 70.7 volt transformers

The **KSI 501-WM** is our smallest wall mount loudspeaker and is designed for fast & easy mounting in drywall and other flat substrates. It is designed for retrofit applications in existing substrates, hence the absence of a backbox. It's a perfect choice for corporate, government, retail and private residences requiring wall mounted loudspeakers with high end performance and pleasing architectural appearance.

The **501-WM** offers smooth midrange and bass response through the use of our 5.25" bass-mid transducer. Our 5.25" transducer provides exceptional voice reproduction making the **501-WM** a fine loudspeaker for video and dialogue applications. Our 1" pure titanium dome tweeter gives the **501-WM** outstanding clarity and coherence with wide frequency response and moderate power capacity. Mounting is fast & easy with our continuous compression clamps. After a cutout of 10" h x 6" w is made, fiberglass damping is added to the wall cavity to provide smoother frequency response. Simply wire the **501-WM**, place it through the opening and tighten the clamps. Snap on the grille and your finished! This fast installation procedure is ideal for facilities where down time is a paramount concern.

All **KSI ceiling and wall mount loudspeakers** may be used in combination with the **501-WM**, providing unlimited solutions for your audio environment. Finally, all **KSI** loudspeakers are completely assembled, saving you precious time and money for fast and easy installation.

KSI's full selection of transformers & accessories make it easy to complete your installation!!



KSI Professional

3500 Parkdale Ave., Baltimore, MD. 21211 410-383-2167