

601-WM

Series III Wall Mount Loudspeaker

- **Very Smooth Frequency Response**
- **Fast & Easy to Install**
- **Fully Assembled**
- **Cost Effective**

The grille on the 601-WM is acoustically transparent and will blend with any decor.

The **KSI 601-WM** is a mid sized wall mount loudspeaker designed for fast & easy mounting in drywall and other flat substrates. It is designed for retrofit applications in existing substrates, hence the absence of a backbox. It's a perfect choice for corporate, government, retail and private residences requiring wall mounted loudspeakers with high end performance and pleasing architectural appearance.

The **601-WM** offers smooth midrange and bass response through the use of our 6.5" bass-mid transducer. Our 6.5" transducer provides exceptional voice reproduction making the **601-WM** a fine loudspeaker for video and dialogue applications. Our 1" pure titanium dome tweeter gives the **601-WM** outstanding clarity and coherence with wide frequency response and moderate power capacity. Mounting is fast & easy with our continuous compression clamps. After a cutout of 12" h x 7" w is made, fiberglass damping is added to the wall cavity to provide smoother frequency response. Simply wire the **601-WM**, place it through the opening and tighten the clamps. Snap on the grille and your finished! This fast installation procedure is ideal for facilities where down time is a paramount concern.

All **KSI ceiling and wall mount loudspeakers** may be used in combination with the **601-WM**, providing unlimited solutions for your audio environment. Finally, all **KSI** loudspeakers are completely assembled, saving you precious time and money for fast and easy installation.

KSI's full selection of transformers & accessories make it easy to complete your installation!!



Specifications

Frequency Response	55-20,000 HZ +/- 4 db
Sensitivity	91 db (1w/1m)
Power Capacity, watts	50 RMS; 100 Program
Crossover Frequency	3500 HZ @ 6db/octave
Nominal Impedance	8 ohms
Nominal Dispersion	At least 110 degrees up to 6000 HZ
Low Frequency Transducer	6.5" - 1.5" voice coil
High Frequency Transducer	1" titanium dome
Enclosure Type	No backbox
Cutout Mounting Dimensions	12" h x 7" w
Enclosure Dimensions	13.5" h x 8.5" w x 2.5" d
Exposed Grill Dimensions	13.5" h x 8.5" w x .5" d
Baffle Construction	1/2" 9 ply Baltic birch
Mounting System	KSI continuous compression clamps
Finish	White grille & baffle
Electrical Input	Hardwire input
Weight	5 lbs.
Options	25 & 70.7 volt transformers



KSI Professional

3500 Parkdale Ave., Baltimore, MD. 21211 410-383-2167