


601-WMBB

Series III Wall Mount Loudspeaker with Backbox

- **Very Smooth Frequency Response**
- **Easy to Install**
- **Fully Assembled**
- **Cost Effective**



The grille on the 601-WMBB is acoustically transparent and will blend with any decor.



The **KSI 601-WMBB** is a mid sized wall mount loudspeaker with a rear backbox designed for clean mounting in drywall and other flat substrates. It's a perfect choice for corporate, government, retail, private residences and any installation demanding superb sound quality with pleasing architectural appearance.

The **601-WMBB** offers smooth midrange and bass response through the use of our 6.5" bass-mid transducer and 8" optimally tuned passive radiator. Our 6.5" transducer provides exceptional voice reproduction making the **601-WMBB** a fine loudspeaker for video and dialogue applications. Our 1" pure titanium dome tweeter gives the **601-WMBB** outstanding clarity and coherence with wide frequency response and moderate power capacity. The backbox is designed to mount into a 2x4 wall cavity on 16" centers prior to the drywall installation. The drywall installer simply trims out the backbox opening as with any light fixture or outlet. After painting and finishing of the drywall, the **601-WMBB** baffle can be quickly reinstalled into the opening to complete the job.

All **KSI ceiling and wall mount loudspeakers** may be used in combination with the **601-WMBB**, providing unlimited solutions for your audio environment. And as an option for installations requiring a fire retardant product, all **Series III** wall mount backboxes are also available fabricated from UL listed fire retardant particle board. Finally, all **KSI** loudspeakers are completely assembled, saving you precious time and money for fast and easy installation.

KSI's full selection of transformers & accessories make it easy to complete your installation!!



Specifications

Frequency Response	50-20,000 HZ +/- 3 db
Sensitivity	91 db (1w/1m)
Power Capacity, watts	50 RMS; 100 Program
Crossover Frequency	3500 HZ @ 6db/octave
Nominal Impedance	8 ohms
Nominal Dispersion	At least 110 degrees up to 6000 HZ
Low Frequency Transducer	6.5" - 1.5" voice coil
High Frequency Transducer	1" titanium dome
Tuning	8" passive radiator
Enclosure Type	Optimally vented
Enclosure Dimensions	26" h x 14" w x 3.5" d
Exposed Grill Dimensions	21" h x 10" w x 1/2" d
Enclosure Construction	1/2" particle board w/internal stiffeners
Finish	White grille w/backbox
Electrical Input	Hardwire input
Weight	24 lbs.
Options	25 & 70.7 volt transformers UL Fire rated particle board



KSI Professional

3500 Parkdale Ave., Baltimore, MD. 21211 410-383-2167