

6061-CSD

Series III 2x2 Grid Ceiling Mount Loudspeaker

- Very Smooth Frequency Response
- Fast & Easy to Install
- Fully Assembled
- Cost Effective



The 6061-CSD looks great in any 2x2 ceiling. KSI's acoustically transparent grille blends with any decor.

The **KSI 6061-CSD** is the companion to our **6061-CS** and a smaller version of our popular **8081-CSD**. KSI's unique and innovative loudspeakers are right at home in corporate, government, institutional and retail installations which benefit from the superb sound quality and pleasing architectural appearance.

The **6061-CSD** offers smooth midrange performance with powerful bass response through the use of our 6.5" bass-mid transducer and 8" optimally tuned passive radiator. **KSI's** 6.5" transducer renders exceptional voice reproduction for improved intelligibility. The addition of our 1" pure titanium dome tweeter produces exceptionally clean sound reproduction and wide frequency response with moderate power capacity. To further enhance the low frequency and midrange performance of the **6061-CSD**, we have included our anti-resonance fabrication for the backbox enclosure. Our state of the art CNC machinery gives us the ability to produce an incredibly strong, vibration free and low weight enclosure, which greatly improves sound quality over the entire spectrum. The front baffle is precisely angled to render accurate imaging and spatial detail, which assures faithful reproduction of dialogue and complex digital audio when used in a left, center and right configuration for video. And because the **6061-CSD** only protrudes 8" from the ceiling, its sure not to get in your way.

All **KSI ceiling and wall mount loudspeakers** may be used in combination with the **6061-CSD**, providing unlimited solutions for your audio environment. And as an option for installations requiring a fire retardant product, all **Series III ceiling loudspeakers** are also available fabricated from UL listed fire retardant particle board. Finally, all **KSI** loudspeakers are completely assembled, saving you precious time and money for fast and easy installation.

KSI's full selection of transformers & accessories make it easy to complete your installation!!



Specifications

Frequency Response	50-20,000 HZ +/- 3 db
Sensitivity	91 db (1w/1m)
Power Capacity, watts	50 RMS; 100 Program
Crossover Frequency	3500 HZ @ 6db/octave
Nominal Impedance	8 ohms
Nominal Dispersion	At least 110 degrees up to 6000 HZ
Low Frequency Transducer	6-1/2" 1-1/2" voice coil
High Frequency Transducer	1" titanium dome
Tuning	8" passive radiator
Enclosure Type	Optimally vented
Enclosure Dimensions	23-5/8" h x 23-5/8" w x 8" d
Enclosure Construction	1/2" particle board w/internal stiffeners
Finish	White grille w/white backbox
Electrical Input	Hardwire input
Weight	21 lbs.
Options	25 & 70.7 volt transformers UL Fire rated particle board



KSI Professional

3500 Parkdale Ave., Baltimore, MD. 21211 410-383-2167