


801-WM

Series III Wall Mount Loudspeaker

- **Very Smooth Frequency Response**
- **Fast & Easy to Install**
- **Fully Assembled**
- **Cost Effective**



The grille on the 801-WM is acoustically transparent and will blend with any decor.



Specifications

| | |
|----------------------------|------------------------------------|
| Frequency Response | 50-20,000 HZ +/- 4 db |
| Sensitivity | 92 db (1w/1m) |
| Power Capacity, watts | 50 RMS; 100 Program |
| Crossover Frequency | 3500 HZ @ 6db/octave |
| Nominal Impedance | 8 ohms |
| Nominal Dispersion | At least 110 degrees up to 6000 HZ |
| Low Frequency Transducer | 8" - 1.5" voice coil |
| High Frequency Transducer | 1" titanium dome |
| Enclosure Type | No backbox |
| Cutout Mounting Dimensions | 15.5" h x 10.5" w |
| Enclosure Dimensions | 15.5" h x 10.5" w x 3.5" d |
| Exposed Grill Dimensions | 15.5" h x 10.5" w x .5" d |
| Baffle Construction | 1/2" 9 ply Baltic birch |
| Mounting System | KSI continuous compression clamps |
| Finish | White grille & baffle |
| Electrical Input | Hardwire input |
| Weight | 7 lbs. |
| Options | 25 & 70.7 volt transformers |

The **KSI 801-WM** is the wall mount companion to our popular **8081-CS** for fast & easy mounting in drywall and other flat substrates. It is designed for retrofit applications in existing substrates, hence the absence of a backbox. It's a perfect choice for corporate, government, retail and private residences requiring wall mounted loudspeakers with high end performance and pleasing architectural appearance.

The **801-WM** offers smooth midrange and bass response through the use of our 8" bass-mid transducer. Our 8" transducer provides exceptional voice reproduction making the **801-WM** a fine loudspeaker for video, music and dialogue applications. Our 1" pure titanium dome tweeter gives the **801-WM** outstanding clarity and coherence with wide frequency response and moderate power capacity. Mounting is fast & easy with our continuous compression clamps. After a cutout of 14" h x 9" w is made, fiberglass damping is added to the wall cavity to provide smoother frequency response. Simply wire the **801-WM**, place it through the opening and tighten the clamps. This fast installation procedure is ideal for facilities where down time is a paramount concern.

All **KSI ceiling and wall mount loudspeakers** may be used in combination with the **801-WM**, providing unlimited solutions for your audio environment. Finally, all **KSI** loudspeakers are completely assembled, saving you precious time and money for fast and easy installation.

KSI's full selection of transformers & accessories make it easy to complete your installation!!



KSI Professional

3500 Parkdale Ave., Baltimore, MD. 21211 410-383-2167