



8081-CSD-SW

Frequency Response	48-20,000 HZ +/- 3 db
Sensitivity	92 db (1w/1m)
Power Capacity, Watts	50 RMS; 100 Program
Crossover Frequency	3500 HZ passive
Nominal Impedance	8 ohms
Nominal Dispersion	At least 110 degrees up to 6000 HZ
Low Frequency Transducer	8" 1-1/2" voice coil
High Frequency Transducer	1" titanium dome
Tuning	10" passive radiator
Enclosure Type	Optimally vented
Manual Swivel Adjustment	90 degrees nominal, up to 360 degrees
Enclosure Dimensions	23-5/8" h x 23-5/8" w x 10" d
Enclosure Construction	1/2" MDF lite board w/internal stiffeners
Finish	White grille w/white backbox
Electrical Input	Hardwire input
Weight	24 lbs.
Options	25 & 70.7 volt transformers Duraflake Fire rated particle board

The **8081-CSD-SW 2x2** grid adjustable swivel ceiling mount loudspeaker is a high fidelity loudspeaker and the companion to our popular 8081-CS. The unique and innovative design of the **8081-CSD-SW** makes it a perfect choice for corporate, government, retail and any installation demanding superb sound quality with pleasing architectural appearance.

The **8081-CSD-SW** allows the user precise control of the acoustical sound field through the use of KSI's innovative adjustable swivel mounting system. Up until now, our 2x2 CSD loudspeakers have been limited to the alignment of the ceiling grid to determine which direction they fire. Now, you can adjust the loudspeaker around a 360 degree center axis, thereby guaranteeing optimal acoustical performance. Adjustments are made simple and quick with the use of a standard hex wrench. Once the angle of adjustment has been determined, the installer simply tightens a single securing bolt to lock the **8081-CSD-SW** in place. This unique feature will permit all of your ceiling installations to have the same high end performance as swivel wall mount systems with the simplicity of a ceiling mount installation.

The **8081-CSD-SW** offers the same audio specifications and performance as the 8081-CSD, assuring you of KSI's unparalleled quality and value.

All KSI ceiling and wall mount loudspeakers may be used in combination with the **8081-CSD-SW**, providing unlimited solutions for your audio environment. The **8081-CSD-SW** is available fabricated from UL listed Duraflake particle board by ordering part number **8081-CSD-SW-FR**.

Applications

- Corporations
- AV Theaters & surround Sound
- Schools & Universities
- Government Installations
- Retail

Features

- Manually swivels up to 360 degrees for precise acoustical sound fields
- High Power Capacity
- Wide and Even Dispersion
- Very Wide Frequency Response
- Ready to Install
- Grille Included



List Price: \$486.00 each
List Price-FR Model: \$584.00 each