

KSI Low Frequency Loudspeakers

SERIES III

Features
Applications

- Premium Audio Performance
- Extended Frequency Response
- High SPL Output
- High Power Capacity
- Optimum Tuned Enclosure
- Fully Assembled

- Foreground Music Systems
- Corporate Board Rooms
- Government Installations
- Special Effects
- Surround Sound Systems



12-1S

Frequency Response	40-250 HZ +/- 3db
Sensitivity	93 db 1w/1m
Power, Watts	150 RMS 290 Program
Impedance	8 Ohms
Woofer	12" cast frame 2" voice coil
Tuning	3" tuned port
Dimensions HxWxD	23.625" x 23.625" x 10"
Weight	48 lbs



12-2S

Frequency Response	40-800 HZ +/- 3db
Sensitivity	95 db 1w/1m
Power, Watts	300 RMS 580 Program
Impedance	4 Ohms
Woofer	2-12" cast frame w/ 2" voice coil
Tuning	coil
Dimensions HxWxD	20" x 33" x 18"
Weight	79 lbs



15-1S

Frequency Response	35-500 HZ +/- 3db
Sensitivity	92 db 1w/1m
Power, Watts	200 RMS 350 Program
Impedance	8 Ohms
Woofer	15" w/ 2.5" voice coil
Tuning	optimally vented tuned port
Dimensions HxWxD	24" x 22" x 225"
Weight	72 lbs



15-2S

Frequency Response	35-500 HZ +/- 3db
Sensitivity	90 db 1w/1m
Power, Watts	400 RMS 700 Program
Impedance	4 Ohms
Woofer	2-15" w/ 2.5" voice coil
Tuning	optimally vented tuned port
Dimensions HxWxD	24" x 44" x 22"
Weight	115 lbs



210-S

Frequency Response	41-290 HZ +/- 4db
Sensitivity	94 db 1w/1m
Power, Watts	200 RMS 300 Program
Impedance	4 Ohms
Woofer	2-10" w/ 2.5" voice coil
Tuning	optimally vented tuned port
Dimensions HxWxD	28" x 18" x 15"
Weight	78 lbs

www.ksipro.com