

Features

- Premium Audio Performance
- Wide Frequency Response
- Very Low Insertion Loss
- Up to 100 watts
- A Must for KSI Loudspeakers

KSI audio transformers are designed for use in 70.7 volt distributed sound systems. Heavy steel cores assure very low distortion and wide frequency response. This is essential, as our transformers will not degrade the high performance found in all KSI loudspeakers. Compared to small cheap transformers from other manufactures, KSI transformers are of consistent and high quality, providing you with top audio performance for all of your distributed sound systems. Our ELT series provides exceptional performance by offering extended low frequency response.

The response over the entire range only varies by only 1 db!! KSI offers a full selection of sizes for any installation.

TRANSFORMER SPECIFICATIONS				
70 Volt line standard transformers				
T70-8	T70-15	T70-30	T70-60	T70-100
70 Volt line extended low transformers				
ELT70-8	ELT70-15	ELT70-30	ELT70-60	
<i>All extended low frequency transformers are special order only.</i>				
Primary Taps Watts				
2,4,8	5,10,15	7.5,15,30	15,30,60	25,50,100
Frequency response				
T series/ 50-15000 Hz +/- 3db				
ELT series/ 30-15000 Hz +/- 1db				
Insertion loss				
All transformers .5db				
Secondary impedance				
All transformers 4 & 8 ohms				

