

Features

Applications

- Unbelievable Audio Performance
- High Power Capacity
- Wide and Even Dispersion
- Ready to Install
- Wall and Ceiling Mount
- Grille Included

- Corporations
- A-V Theaters & Surround Sound
- Schools & Universities
- Government Installations
- Residential Installations



501-WM

Frequency Response	60-20,000 HZ +/- 4db
Sensitivity	90 db 1w/1m
Power, Watts	50 RMS 90 Program
Impedance	8 Ohms
Woofer	5.25"/1.25" v.c.
Tweeter	1" Titanium Dome
Dimensions HxWxD	11.5" x 7.5" x 2.5"
Weight	4lbs



601-WM

Frequency Response	55-20,000 HZ +/- 4db
Sensitivity	91 db 1w/1m
Power, Watts	50 RMS 100 Program
Impedance	8 Ohms
Woofer	6.5"/1.5" v.c.
Tweeter	1" Titanium Dome
Dimensions HxWxD	13.5" x 8.5" x 2.5"
Weight	5lbs



501-WMBB

Frequency Response	55-20,000 HZ +/- 3db
Sensitivity	90 db 1w/1m
Power, Watts	50 RMS 90 Program
Impedance	8 Ohms
Woofer	5.25"/1.25" v.c.
Tweeter	1" Titanium Dome
Tuning	8" passive radiator
Backbox Grille	22.5" x 14" x 3.5" 18" x 10"
Weight	21lbs



601-WMBB

Frequency Response	50-20,000 HZ +/- 3db
Sensitivity	91 db 1w/1m
Power, Watts	50 RMS 100 Program
Impedance	8 Ohms
Woofer	6.5"/1.5" v.c.
Tweeter	1" Titanium Dome
Tuning	8" passive radiator
Backbox Grille	26" x 14" x 3.5" 21" x 10"
Weight	24lbs



801-WMBB

Frequency Response	48-20,000 HZ +/- 3db
Sensitivity	92 db 1w/1m
Power, Watts	50 RMS 100 Program
Impedance	8 Ohms
Woofer	8"/1.5" v.c.
Tweeter	1" Titanium Dome
Tuning	10" passive radiator
Backbox Grille	32" x 14" x 5.5" 24.5" x 12.5"
Weight	28lbs

KSI Wall & Ceiling Mount Loudspeakers

SERIES III



801-WM

Frequency Response	50-20,000 HZ +/- 4db
Sensitivity	92 db 1w/1m
Power, Watts	50 RMS 100 Program
Impedance	8 Ohms
Woofer	8"/1.5" v.c.
Tweeter	1" Titanium Dome
Dimensions HxWxD	15.5" x 10.5" x 3.5"
Weight	7lbs



811-WM

Frequency Response	45-20,000 HZ +/- 4db
Sensitivity	93 db 1w/1m
Power, watts	125 RMS 200 Program
Impedance	8 Ohms
Woofer	8"/1.5" v.c. Cast Frame
Tweeter	25mm Horn Loaded Fabric Dome
Dimensions HxWxD	15.5" x 10.5" x 3.5"
Weight	12lbs



See page 9 for transformers to be used with premium distributed systems.



811-WMBB

Frequency Response	45-20,000 HZ +/- 3db
Sensitivity	93 db 1w/1m
Power, Watts	125 RMS 200 Program
Impedance	8 Ohms
Woofer	8"/1.5" v.c. Cast frame
Tweeter	25mm horn loaded Fabric Dome
Tuning	10" passive radiator
Backbox Grille	32" x 14" x 5.5" 24.5" x 12.5"
Weight	28lbs



811-SBWM

Frequency Response	40-500 HZ +/- 3db
Sensitivity	93 db 1w/1m
Power, Watts	125 RMS 200 Program
Impedance	8 Ohms
Woofer	8"/2" v.c. Cast frame
Tweeter	None
Tuning	10" passive radiator
Backbox Grille	32" x 14" x 5.5" 24.5" x 12.5"
Weight	27lbs



FIRE Retardant

All Series III ceiling loudspeakers are also available fabricated from UL listed fire retardant particle board. Typical lead time for KSI's FR loudspeakers is 1 week.

Unsure about how to design your system?

Call us, we'll help you design the system that is right for your environment.