

Features

Applications

Unbelievable Audio Performance
 High Power Capacity
 Wide and Even Dispersion
 Very Wide Frequency Response
 Ready to Install
 Grille Included

Corporations
 A-V Theaters & Surround Sound
 Schools & Universities
 Government Installations
 Retail Establishments



8081-CSD

Frequency Response	48-20,000 HZ +/- 3db
Sensitivity	92 db 1w/1m
Power, Watts	50 RMS 100 Program
Impedance	8 Ohms
Woofer	8"/1.5" v.c.
Tweeter	1" Titanium Dome
Tuning	10" passive radiator
Dimensions HxWxD	23.625" x 23.625" x 10"
Weight	24lbs



8081-CS

Frequency Response	48-20,000 HZ +/- 3db
Sensitivity	92 db 1w/1m
Power, watts	50 RMS 100 Program
Impedance	8 Ohms
Woofer	8"/1.5" v.c.
Tweeter	1" Titanium Dome
Tuning	10" passive radiator
Dimensions HxWxD	23.625" x 23.625" x 5.5"
Weight	24lbs



6061-CSD

Frequency Response	50-20,000 HZ +/- 3db
Sensitivity	91 db 1w/1m
Power, Watts	50 RMS 100 Program
Impedance	8 Ohms
Woofer	6.5"/1.5" v.c.
Tweeter	1" Titanium Dome
Tuning	8" passive radiator
Dimensions HxWxD	23.625" x 23.625" x 8"
Weight	23lbs



6061-CS

Frequency Response	50-20,000 HZ +/- 3db
Sensitivity	91 db 1w/1m
Power, Watts	50 RMS 100 Program
Impedance	8 Ohms
Woofer	6.5"/1.5" v.c.
Tweeter	1" Titanium Dome
Tuning	8" passive radiator
Dimensions HxWxD	23.625" x 23.625" x 4"
Weight	21lbs



8081-CSDHP

Frequency Response	48-20,000 HZ +/- 3db
Sensitivity	93 db 1w/1m
Power, Watts	125 RMS 200 Program
Impedance	8 Ohms
Woofer	8"/1.5" v.c. Cast frame
Tweeter	25mm horn loaded Fabric Dome
Tuning	10" passive radiator
Dimensions HxWxD	23.625" x 23.625" x 10"
Weight	28lbs



8081-CSHP

Frequency Response	45-20,000 HZ +/- 3db
Sensitivity	93 db 1w/1m
Power, Watts	125 RMS 200 Program
Impedance	8 Ohms
Woofer	8"/1.5" v.c. Cast frame
Tweeter	25mm horn loaded Fabric Dome
Tuning	10" passive radiator
Dimensions HxWxD	23.625" x 23.625" x 5.5"
Weight	28lbs