

KSI High Fidelity Near Field Loudspeakers

SERIES III

Features
Applications

- Accurate Reproduction
- Wide and Even Dispersion
- Fully Shielded on the 501-SH
- Cost Effective
- Free Standing — Plug in and enjoy!
- Gold Plated Dual Binding Posts

- Foreground Music Systems
- Corporate Board Rooms
- Government Installations
- Houses of Worship
- Hotels & Airports
- Home Theater Systems




Our wall mount brackets make mounting any of our near field loudspeakers fast and safe. They may be ordered pre-mounted or may be mounted in the field.



501-SH

Frequency Response	55-20,000 HZ +/- 3db
Sensitivity	90 db 1w/1m
Power Watts	50 RMS 90 Program
Impedance	8 Ohms
Woofer	5.25"/1.25" v.c.
Tweeter	1" Titanium Dome
Tuning	8" passive radiator
Dimensions HxWxD	18" x 8.5" x 7.5"
Weight	14lbs



601

Frequency Response	50-20,000 HZ +/- 3db
Sensitivity	91 db 1w/1m
Power Watts	50 RMS 90 Program
Impedance	8 Ohms
Woofer	6.5"/1.5" v.c.
Tweeter	1" Titanium Dome
Tuning	8" passive radiator
Dimensions HxWxD	19.5" x 8.5" x 8"
Weight	16lbs



801

Frequency Response	48-20,000 HZ +/- 3db
Sensitivity	92 db 1w/1m
Power Watts	50 RMS 100 Program
Impedance	8 Ohms
Woofer	8"/1.5" v.c.
Tweeter	1" Titanium Dome
Tuning	10" passive radiator
Dimensions HxWxD	23" x 11" x 10"
Weight	24lbs



811-HP

Frequency Response	45-20,000 HZ +/- 3db
Sensitivity	93 db 1w/1m
Power, Watts	125 RMS 200 Program
Impedance	8 Ohms
Woofer	8"/1.5" v.c. cast frame
Tweeter	25mm horn loaded fabric dome
Tuning	10" passive radiator
Dimensions HxWxD	23" x 11" x 10"
Weight	28lbs